

Borel

Standard Furnaces & Ovens

since 1918



SMALL MELTING FURNACES

1100°C

KP 1100

Use: Removable crucible furnace for melting or maintaining melted state of non-ferrous metals.

Construction: Access to crucible from top, manual cover closing.

Insulation: Multilayer insulation with double thickness of ceramic fibre.

Electric: Single-phase 230 VAC, 50 Hz.

Heating: Heating muffle.

Regulation: Digital PID temperature controller.

Documentation: CE marking and operating instructions in English.

Delivered with: 1 crucible handling tongs, 1 crucible with pouring lip.



Photos for illustration purposes only



MODEL	ITEM CODE	Int. Vol. (L)	Acceptable mass (kg)	Crucible Dim. (Ø x h) (mm)	Ext. Dim. (WxHxD) (mm)	Power (kW)	Weight (kg)
KP 1100-1	N11341	0.11	1	Ø41 x 110	230 x 340 x 220	0.7	5.8
KP 1100-3	N11345	0.33	3	Ø52 x 150	270 x 420 x 275	1.4	10.8

SOLO Swiss SA

Grandes-Vies 25, 2900 Porrentruy, Switzerland - Tel. +41 (0)32 756 64 00 - borel@soloswiss.com - www.borelswiss.com

* V 28.01.2022

Specifications subject to change