

Borel

Standard Furnaces & Ovens

since 1918



Photos for illustration purposes only

HIGH TEMPERATURE MELTING FURNACES 1350°C RH 1350

Definition: Removable crucible furnace for melting or maintaining melted state of non-ferrous metals. Handling the crucible with 1 pair of tongs.

Construction: Access to crucible from top, manual cover closing.

Insulation: Multilayer insulation. Interior in ceramic fibre and refractory bricks.

Heating: Electrical coil resistors on 4-6 sides of the furnace. Resistors mounted on ceramic tubes and/or in grooves. The heating is turned off at the opening of the door.

Electricity: Single-phase 230 VAC, 50 Hz.

Regulation: Digital display PID Axron Swiss temperature controller. Analogue display of voltage and amperes. Selector to compensate ageing of heating elements.

Documentation: CE marking and operating instructions in English.

Delivered with:
1 crucible handling tongs, 1 crucible with pouring lip.



MODEL	ITEM CODE	Int. Vol. (L)	Acceptable mass (kg)	Crucible Dim. (Ø x h) (mm)	Ext. Dim. (WxHxD) (mm)	Power (kW)	Weight (kg)
RH 1350-5	N14825	0.75	5	Ø114 x 141	500 x 900 x 530	4.0	85
RH 1350-10	N14826	1.2	10	Ø130 x 165	500 x 950 x 560	5.5	98

SOLO Swiss SA

Grandes-Vies 25, 2900 Porrentruy, Switzerland - Tel. +41 (0)32 756 64 00 - borel@soloswiss.com - www.borelswiss.com

* V 28.01.2022

Specifications subject to change