

Borel

Standard Furnaces & Ovens

since 1918



THERMODRYER OVENS 400°C TR 400

Definition: Forced convection electrical oven for all applications.

Construction: Mild or stainless steel for versions -I, several shelves.

Insulation: Rock wool insulation of all surfaces, including door.

Ventilation: Stainless steel motor ventilator. Adjustable air outlet.

Heating: Battery of shielded electrical resistors.

Electricity: 3x400 VAC.

Regulation: Axron Swiss PID temperature controller, over temperature safety.

Documentation: CE marking and operating instructions in English.

Delivered with: 2 shelves (perforated plates).



Photos for illustration purposes only



MODEL	ITEM CODE	Int. Vol. (L)	Int. Dim. (WxHxD) (mm)	Ext. Dim. (WxHxD) (mm)	Power (kW)	Weight (kg)
TR 400-140	N15973	140	390 x 390 x 900	1140 x 1050 x 1700	8.0	120
TR 400-140-I	N15974	140	390 x 390 x 900	1140 x 1050 x 1700	8.0	120
TR 400-180	N15975	180	555 x 605 x 555	1300 x 1150 x 950	6.0	250
TR 400-180-I	N15976	180	555 x 605 x 555	1300 x 1150 x 950	6.0	250
TR 400-400	N15977	400	700 x 800 x 700	1560 x 1400 x 1540	20	650
TR 400-400-I	N15978	400	700 x 800 x 700	1560 x 1400 x 1540	20	650
TR 400-735	N15979	735	830 x 1490 x 750	1480 x 2400 x 1490	35	1070
TR 400-735-I	N15980	735	830 x 1490 x 750	1480 x 2400 x 1490	35	1070

SOLO Swiss SA

Grandes-Vies 25, 2900 Porrentruy, Switzerland - Tel. +41 (0)32 756 64 00 - borel@soloswiss.com - www.borelswiss.com